



ONYX OXLS4K75SH



ONYX presents a high-brightness LCD advertising solution engineered for challenging light environments like storefront windows. With exceptional luminance far surpassing traditional displays, this ultra-bright screen ensures vivid visibility even under direct sunlight. ONYX integrates a powerful multimedia information release system, combining video, text, and web content into captivating programs delivered across networked terminals. The sleek, durable design supports versatile installation, while advanced driver technology delivers stunning 4K image quality—ideal for impactful, real-time promotions in any high-light or outdoor setting.

Model		OXLS4K75SH
Panel	Display size	75 inch (16:9)
	Display type	LED LCD display
	Screen display size	1655mm x934mm/ 16 : 9
	Physical resolution	3840(H)×2160(V)
	Display color	16.7M
	Brightness	3000 nits
	Contrast	1300:1
	Viewing angle	89°/89°/89°/89°
	Response time	6ms
Main parameters	Additional functions	AUTO-Brightness; Intelligent noise reduction; Fan cooling;
	Physical interface	1 built-in HDMI 1 channel DisplayPort 1 channel HDMI 1 channel DVI 1 channel VGA 1 channel AV 1 channel USB
Machine Features	Shell and appearance	Sheet metal
	Color	Black
	Overall dimensions	1674*953*57.4
	Power supply	AC 100-240V
	Maximum power consumption rate	220W
	Net weight	38 kg
	Gross weight	51 kg
	Installation	Wall-mounted, floor-standing, hanging



Environment	Workplace	Indoor
	Anti-Glare	Support direct sunlight
	Operating humidity	5% - 90%
	Storage humidity	5% - 90%
	Operating temperature	0°C - 50°C
	Storage temperature	-20°C - 60°C
Warranty	Warranty Period	2 Year
	Technical Support	Lifetime

Machine dimensions Unit: mm

