

## CNYX

The ONYX Interactive Whiteboard offers 4K resolution, 20point touch interactivity, and Android/Windows compatibility. Ideal for meetings, teaching, and presentations, its versatile design supports wall mounting, stands, and both vertical or horizontal use, delivering seamless collaboration with a user-friendly interface.



























	Basic Model	
Panel	Display size	65 inch (16:9)
	Display type	LED LCD display
	Screen display size	1428.0 x 803.0mm 【HxV】
	Physical resolution	3840(H)×2160(V)
	Display color	10bit, 1.07B
	Refresh rate	4K-60HZ
	Brightness	350cd/m2
	Contrast	5000:1
	Viewing angle	178°/178°
	Display protection	4mm fully tempered high explosion-proof-anti-glare glass
	Backlight life	50,000 hours
	Touch embed	Built-in one-piece, not plug-in , front detachable design
	Touch embed  Touch sensing technology	Infrared sensing touch recognition technology ( 20 points)
	Touch sensing technology	Infrared sensing touch recognition technology ( 20 points) Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points
	Touch sensing technology  Writing style	Infrared sensing touch recognition technology ( 20 points)  Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points 8mm)
Touch	Touch sensing technology Writing style Cursor speed	Infrared sensing touch recognition technology ( 20 points)  Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points 8mm)  120 points/s
Touch	Touch sensing technology Writing style Cursor speed Positioning accuracy	Infrared sensing touch recognition technology ( 20 points)  Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points 8mm)  120 points/s  More than 90% of the touch area is ±2mm
Touch	Touch sensing technology  Writing style  Cursor speed  Positioning accuracy  Communication Interface	Infrared sensing touch recognition technology ( 20 points)  Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points 8mm)  120 points/s  More than 90% of the touch area is ±2mm  Type B USB male connector
Touch	Touch sensing technology  Writing style  Cursor speed  Positioning accuracy  Communication Interface  Touch resolution	Infrared sensing touch recognition technology ( 20 points)  Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points 8mm)  120 points/s  More than 90% of the touch area is ±2mm  Type B USB male connector  32767*32767
Touch	Touch sensing technology  Writing style  Cursor speed  Positioning accuracy  Communication Interface  Touch resolution  Touches	Infrared sensing touch recognition technology ( 20 points)  Finger, touch pen or other non-transparent object with a diameter of not less than 5mm (multiple points 8mm)  120 points/s  More than 90% of the touch area is ±2mm  Type B USB male connector  32767*32767  Theory unlimited times

	Speaker specifications	10W /8 ohm × 2 speakers
	Operating system	Android 13.0
	CPU	Quad core ARMCortex-A55
	GPU	ARM Mali-G52 MP2 (2EE)
	Memory	4G
	FLASH	32GB
	WiFi	2.4G, 5G
	Bluetooth	Yes
		Network input port: 1  Network output port: 1
	Physical interface	Android USB2.0 ports: 1
		RS232 port: 1
		Touch2.0 ports: 1
Mayn parameters		HDMI IN port: 2 LINE OUT port: 1
Mayn parameters		Full channel USB 3.0 ports: 2
		OPTICAL OUT port: 1
	Front terminal input	Front interface: USB*2 (full channel), type-c*1, HDMI IN*1, TOUCH*1  Front button: one-button power on/off
		Supports full-channel switching touch, touch menu, touch menu
	Other functions	operation, touch volume adjustment, touch brightness adjustment
		Supports sleep timer, shutdown memory
		Supports touch one-key energy saving [i.e. the screen is off and the all-inone machine is in working state, and audio and video can be played
		normally]
		Supports remote control child lock function
		Supports front button one-key switch on and off the computer and TV  Supports touch menu one-key shutdown
		Supports 2.0 channels
		Supports front computer USB3.0 socket
		Supports transfer of external devices using the machine's built-in touch frame function
	Shell and appearance	Al all a form delta forth the forther forther
	Silen and appearance	Aluminum frame design, front buttons, front ports, front speakers
	Color	Aluminum frame design, front buttons, front ports, front speakers  Silver
	Color	Silver
	Color Overall dimensions	Silver 1482.4*895.4*89.5mm
Machine Features	Color Overall dimensions Package Size	Silver 1482.4*895.4*89.5mm 1600*1000*200mm
Machine Features	Color Overall dimensions Package Size net weight	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG
Machine Features	Color Overall dimensions Package Size net weight Gross Weight Power supply	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz
Machine Features	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W
Machine Features	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W
Machine Features	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)
Machine Features	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor
	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C
Machine Features  Environment	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing
	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C
	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensation
	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece
	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces
Environment	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces  1 piece
	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card Touch pen	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces  1 piece  1 piece
Environment	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card Touch pen Certificate	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces  1 piece  1 piece  1 piece
Environment	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card Touch pen Certificate Manual	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece 2 pieces 1 piece 1 piece 1 piece 1 piece
Environment	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card Touch pen Certificate Manual 1.5m power cord	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces  1 piece  1 piece  1 piece  1 piece  1 piece  1 piece
Environment	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card Touch pen Certificate Manual 1.5m power cord	Silver  1482.4*895.4*895.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces  1 piece  1 piece  1 piece  1 piece  1 piece  1 piece  2 Year
Environment  Accessories	Color Overall dimensions Package Size net weight Gross Weight Power supply Maximum power consumption rate Standby power Installation workplace Operating temperature Working humidity Storage temperature Storage humidity Remote control Battery Maintenance card Touch pen Certificate Manual 1.5m power cord	Silver  1482.4*895.4*89.5mm  1600*1000*200mm  40KG  48KG  AC 100-240V, 50/60Hz  ≤135W  ≤0.5W  Standard wall mount (mobile bracket optional)  Indoor  0°C - 40°C  10% - 90% non-condensing  -20°C - 60°C  10% - 90% non-condensation  1 piece  2 pieces  1 piece  1 piece

## Machine dimensions Unit: mm





Additional configurations available			
Camera	1.3mp, 4.8mp, Al automatic tracking		
CPU	i3, i5, i7		
Memory	Standard 4G DDR4, Upgraded to 16G DDR4		
Operating system	Windows 7, Windows 10		
Graphics card	Intel HD Graphics		
Expansion interface	1x MINI-SATA SSD interface		
Microphone	8 microphone arrays, Echo Cancellation, 8-meter ultra-long distance sound pickup effect		



491.2

50D.D